Pan Oston®

SYMPHONY DOUBLE POLE

Application

Self-order, Payment, Digital Signage

Market

Quick Service Restaurants

Purpose


The SYMPHONY self-order terminal is specifically designed to improve every user's experience in the QSR industry! The self-order terminal is easy to install, easy to clean, easy to refill receipts, etc. The SYMPHONY self-order terminal is the high-quality kiosk that puts every user first. From burger-ordering customer up till kiosk service technician, every user counts!



SYMPHONY DOUBLE

Dimensions

Units in mm



Product specs

Туре	Specification	
Power supply	230 VAC - 50/60Hz internally	
	Wire gauge: 1.5mm² - 2.5mm²	
Power consumption	Typical: 100W	
	Maximum: 200W	
Ingress Protection	IP20	
Operating temperature	5°C up to 35°C	
Storage temperature	-10°C up to 50°C	
Humidity	20% up to 80% non-condensing	
Weight*	71.3 kg	

Hardware options

Туре	Specification	
Screen	Pan Oston	27" - Full HD 16:9 PCAP
PC	Windows 10	NUC Celeron
	Android 11	Giada DN74
	Others on request	
Printer	Epson	TM-M30III
Scanner	Newland	FM3080 FM3281
LED Controller	Pan Oston	BrightLight LED controller
Pin & Chip	CCV	A35 Q30 Pad Next
	Ingenico	IPP 320-350 Lane/5000
	Verifone	P400 V400C VX 820
	Worldline	Saturn 1000F2
	Others on request	

Product options

Туре	Description
Mounting options	Fixed to floor - Using bolts
	Fixed to floor - Using adhesive - Additional 600×600 footplate
	Free standing - No bolts/adhesive - Additional 800 x 800 footplate
Power / UTP supply	From floor
	From ceiling - Max. ceiling height = 2840mm If ceiling is higher, additional power poles need to be supplied
Accessories	2x Table Tent Holder
	2x Storm Interface - AudioNav
Colour scheme	Body - Every RAL colour possible
	Ring - Every RAL colour possible

^{*}Depending on configuration and accessories

Pan Oston B.V.

Adress Hertzstraat 1

8102 PK Raalte The Netherlands

P.O. Box P.O. Box 222

8100 AE Raalte The Netherlands

Phone +31572357755
Email info@panoston.nl
Website panoston.nl